



Name: \_\_\_\_\_

Date: \_\_\_\_\_

1. To load on a conveyor truck start from:
  - a. The front of the head board down to the back of the conveyor
  - b. The back of the conveyor to the front of the head board
  - c. The middle of the conveyor to the front of the head board
  - d. The middle of the conveyor to the back of the conveyor
2. Improperly securing a load can result in citations.
  - a. True
  - b. False
3. The load should always be checked with the first:
  - a. 25 miles of your trip
  - b. 100 miles of your trip
  - c. 50 miles of your trip
  - d. 75 miles of your trip
4. Always make sure wheels are "Chocked" before loading.
  - a. True
  - b. False
5. It is okay to place cribbing or outrigger pads on the battery box.
  - a. True
  - b. False
6. Always make sure conveyor is properly secured by using a single strap over the conveyor belt while in transit.
  - a. True
  - b. False
7. Pallets should be positioned on the bed butted against each other with no material in between.
  - a. True
  - b. False



Name: \_\_\_\_\_

Date: \_\_\_\_\_

8. When climbing onto the trailer you can climb up using:
- a. The tires
  - b. The pallets
  - c. The approved ladder
  - d. Never climb onto the trailer
9. Never have your drop or tag axle down when transporting material.
- a. True
  - b. False
10. If you are loading a truck with a crane mounted at the rear of the truck, start at the headboard and load your heaviest products positioned close to the head board and work your way to the back.
- a. True
  - b. False



Exam: **Securing Loads Safely - SS17011AE (11 min.)**

Name: \_\_\_\_\_

Date: \_\_\_\_\_

**ANSWER KEY**

- 1: A**
- 2: A**
- 3: C**
- 4: A**
- 5: B**
- 6: A**
- 7: A**
- 8: C**
- 9: B**
- 10: A**